




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04B 1/10	A1	(11) International Publication Number: WO 99/01946 (43) International Publication Date: 14 January 1999 (14.01.99)
(21) International Application Number: PCT/FI98/00548		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 23 June 1998 (23.06.98)		
(30) Priority Data: 972704 23 June 1997 (23.06.97) FI		
(71) Applicant (for all designated States except US): NOKIA TELECOMMUNICATIONS OY [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).		
(72) Inventors; and		
(75) Inventors/Applicants (for US only): HOTTINEN, Ari [FI/FI]; Ristiniementie 4 D 30, FIN-02320 Espoo (FI). LILLEBERG, Jorma [FI/FI]; Mustaherukkatie 1 A, FIN-90800 Oulu (FI). TOSKALA, Antti [FI/FI]; Väinämöisenkatu 25 A 13, FIN-00100 Helsinki (FI). HOLMA, Harri [FI/FI]; Itätuulenkuja 1 B 32, FIN-02100 Espoo (FI).		
(74) Agent: PATENTTITOIMISTO TEKNOPOLIS KOLSTER OY; c/o Kolster Oy AB, Iso Roorinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).		

(54) Title: RECEPTION METHOD AND RECEIVER



(57) Abstract

The invention relates to a reception method and a receiver in a system comprising in each cell a base station communicating with terminals located in its area. A received signal comprises a sum signal of signals originating from several transmitters. The receiver comprises means (208) for performing interference elimination and a simultaneous multi-user detection to the signal and means (210) for searching signal parameters. In order to reduce the required computational capacity, the receiver further comprises means (210) for removing the effect of the signals of the known users from the received sum signal, and means (210) for estimating the parameters of the unknown signals from a narrowband residual signal.

ABSTRACT

The invention relates to a reception method and a receiver in a system comprising in each cell a base station communicating with terminals located in its area. A received signal comprises a sum signal of signals originating from several transmitters. The receiver comprises means for performing interference elimination and a simultaneous multi-user detection to the signal and means for searching signal parameters. In order to reduce the required computational capacity, the receiver further comprises means for removing the effect of the signals of the known users from the receives sum signal, and means for estimating the parameters of the unknown signals from a narrowband residual signal.